








**DEHUMIDIFIER**

<b>Pictures</b>							
	<b>Model</b>	AT-610EB	AT-618EB/AT-618RB	AT-630EB	AT-650EB	AT-690EB	AT-6120EB
<b>Capacity (L/d)</b>	10	18	30	50	90	120	180
<b>Dehumidify area (height * acreage)</b>	2.6m*(15m <sup>2</sup> ~25m <sup>2</sup> )	2.6m*(25m <sup>2</sup> ~35m <sup>2</sup> )	2.6m*(40m <sup>2</sup> ~46m <sup>2</sup> )	2.6m*(50m <sup>2</sup> ~65m <sup>2</sup> )	2.6m*(60m <sup>2</sup> ~100m <sup>2</sup> )	2.6m*(80m <sup>2</sup> ~140m <sup>2</sup> )	2.6m*(80m <sup>2</sup> ~140m <sup>2</sup> )
<b>Power</b>	220V~50HZ	220V~50HZ	220V~50HZ	220V~50HZ	220V~50HZ	220V~50HZ	380V~50HZ
<b>Refrigerant</b>	R134a	R134a	R134a/R407c/R22	R134a/R407c/R22	R134a/R407c/R22	R134a/R407c/R22	R134a/R407c/R22
<b>Input power (W)</b>	220	420	650	850	1500	1850	3000
<b>Working Temp (°C)</b>	5~35	5~35	5~35	5~35	5~35	5~35	5~35
<b>Water tank capacity (L)</b>	2.4	4	6	6	/	/	/
<b>Compressor brand</b>	SHANGHAI HITACHI ( ROTARY )	SHANGHAI HITACHI ( ROTARY )	SHANGHAI HITACHI ( ROTARY )	SHANGHAI HITACHI ( ROTARY )	SHANGHAI HITACHI ( ROTARY )	SHANGHAI HITACHI ( ROTARY )	SHANGHAI HITACHI ( ROTARY )
<b>Compressor protection</b>	Y	Y	Y	Y	Y	Y	Y
<b>Drainage method</b>	water tank	water tank	water tank	water tank	1.5 m drain pipe	1.5 m drain pipe	1.5 m drain pipe
<b>Net dimension (mm)</b>	360X140X440	285X300X585	350X445X600	350X445X600	480X420X960	600X328X1000	650X450X1440
<b>Packing dimension (mm)</b>	420X220X520	400X350X640	540X450X650	540X450X650	560X487X1098	691X454X1114	810X620X1670
<b>Net weight (kg)</b>	8.5	13	24	25	49	60	80
<b>Gross weight (kg)</b>	10	16	27	28	53	65	100
<b>Noise ( dB )</b>				50	56	58	60
<b>Approval</b>	CE/EMC	CE/EMC	CE/GS/EMC	CE/GS/EMC			
	ALL THE PARTS OF DEHUMIDIFIER IS ACCORDING TO ROHS APPROVAL FOR EACH TYPE.						
<b>Container loading (20'/40'HQ)</b>	540/1100	270/576	160/345	160 / 345	88 / 184	80 / 160	25 / 43
<b>Other features</b>	Digital display for environment humidity, computer control dehumidify and defrost, four types dehumidify, saving power, adjustable wind speed, three minutes protection for compressor, overflow protection alarm, universal wheels easy for moving						